



KMR Cordless coil magazin screwdriver for srew rolls 40-80 mm

12600170



SCOPE OF OPERATION

- Timber construction
- Timber frame construction
- Wood packaging
- Measurement and assembly construction
- Terrace, path and garden
- Dry and interior extension
- Carpentry
- Prefabricated house construction

PRODUCT STRENGTHS

- Tool-free depth control
- Includes 2nd battery
- Includes metal case big
- Multiflexible use thanks to additional accessories

SCOPE OF DELIVERY

- Sparepart list
- Service Instructions
- Second battery pack
- Battery charger
- Metal case big

TECHNISCHE DATEN

Types of fastener	Coil screws
Length fastener	40-80 mm
Magazine capacity max	125125 pieces
Depth Adjustment	yes
Tool (LxWxH)	450x76x260 mm
Battery type	Li-ion
Battery capacity	4 Ah
Battery voltage	18 V
RPM	0-3200 rpm
Torque max	16 Nm
Declaration of conformity	CE, UKCA, EAC
Noise characteristic L pA, 1s according to EN 12549	78 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	86 dB(A)
Vibration value ahd according to ISO 8662	2,5 m/s ²



KMR Cordless coil magazin screwdriver for srew rolls 40-80 mm

12600170

SUITABLE FASTENER

Coil screws



Art.-Nr.	Length	Diameter	Material	Thread type	Screw drive
10600129	80 mm	5 mm	Steel, galvanized	Partial thread	TX25
10600454	60 mm	5 mm	Steel, galvanized	Full thread	TX20
10600456	50 mm	4,5 mm	Stainless Steel (1.4301, A2)	Partial thread	TX20
10600471	50 mm	4,5 mm	Steel, galvanized	Partial thread	TX20
10600472	55 mm	4,5 mm	Stainless Steel (1.4301, A2)	Partial thread	TX20
10600473	55 mm	4,5 mm	Steel, galvanized	Partial thread	TX20
10600477	80 mm	5 mm	Steel, galvanized	Partial thread	TX20
10600478	60 mm	5 mm	Stainless Steel (1.4301, A2)	Partial thread	TX20
10600479	70 mm	5 mm	Stainless Steel (1.4301, A2)	Partial thread	TX20
10600488	50 mm	4,5 mm	Steel, galvanized	Partial thread	TX20
10600489	55 mm	4,5 mm	Steel, galvanized	Partial thread	TX20
10600491	65 mm	5 mm	Steel, galvanized	Partial thread	TX25
10600524	60 mm	5 mm	Steel, galvanized	Partial thread	TX20
10600471	50 mm	4,5 mm	Steel, galvanized	Partial thread	TX20
10600488	50 mm	4,5 mm	Steel, galvanized	Partial thread	TX20