



KMR Cordless coil magazin screwdriver for srew rolls 25-50 mm

12600171



SCOPE OF OPERATION

- Timber construction
- Timber frame construction
- Wood packaging
- Measurement and assembly construction
- Terrace, path and garden
- Dry and interior extension
- Carpentry
- Prefabricated house construction

PRODUCT STRENGHTS

- Tool-free depth control
- Includes 2nd battery
- Includes metal case small
- Multiflexible use thanks to additional accessories

SCOPE OF DELIVERY

- Sparepart list
- Service Instructions
- Second battery pack
- Battery charger
- Metal case small

TECHNISCHE DATEN

Types of fastener	Coil screws
Length fastener	25-50 mm
Magazine capacity max	167 pieces
Depth Adjustment	yes
Tool (LxWxH)	390x76x260 mm
Battery type	Li-ion
Battery capacity	4 Ah
Battery voltage	18 V
RPM	0-3200 rpm
Torque max	16 Nm
Declaration of conformity	CE, UKCA, EAC
Noise characteristic L pA, 1s according to EN 12549	78 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	86 dB(A)
Vibration value ahd according to ISO 8662	2,5 m/s ²



KMR Cordless coil magazin screwdriver for srew rolls 25-50 mm

12600171

SUITABLE FASTENER

Coil screws



Art.-Nr.	Length	Diameter	Material	Thread type	Screw drive
10600119	35 mm	4 mm	Steel, galvanized	Partial thread	TX20
10600120	40 mm	4 mm	Steel, galvanized	Partial thread	TX20
10600121	45 mm	4 mm	Steel, galvanized	Partial thread	TX20
10600459	25 mm	4 mm	Steel, galvanized	Partial thread	TX20
10600460	30 mm	4 mm	Stainless Steel (1.4301, A2)	Partial thread	TX20
10600462	34 mm	4 mm	Stainless Steel (1.4301, A2)	Partial thread	TX20
10600463	34 mm	4 mm	Steel, galvanized	Partial thread	TX20
10600464	40 mm	4 mm	Steel, galvanized	Partial thread	TX20
10600465	45 mm	4 mm	Stainless Steel (1.4301, A2)	Partial thread	TX20
10600467	45 mm	4 mm	Steel, galvanized	Partial thread	TX20
10600468	50 mm	4 mm	Steel, galvanized	Partial thread	TX20
10600471	50 mm	4,5 mm	Steel, galvanized	Partial thread	TX20
10600487	50 mm	4 mm	Steel, galvanized	Partial thread	TX20
10600488	50 mm	4,5 mm	Steel, galvanized	Partial thread	TX20
10600500	30 mm	4 mm	Steel, galvanized	Partial thread	TX20